

Convection Oven Gas Convection Oven, 6 GN1/1

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



240470 (ZFCG61CSAS)

Convection oven crosswise,
6x1/1GN, gas

Short Form Specification

Item No. _____

Convection oven with direct steam. Main structure in stainless steel. Cooking chamber with side lighting and drip tray. Double glass door. Heating via atmospheric burners with flame failure device. Main burner with pilot light and piezoelectric ignition. Electromechanical thermostat; temperature adjustable from 30°C to 300°C. Timer from 0 to 120 minutes with acoustic alarm. 5-level humidity control.

Supplied with n. 1 "cross-wise" tray rack composed by 2 side hangers, 60 mm pitch, for 6x1/1GN grids.

Main Features

- Main switch/Cooking mode selector which can be used to set: ON/OFF, hot air without humidification and hot air with humidification (choice of 5 different humidity levels).
- Rapid cooling of oven cavity.
- Timer to set the cooking time, adjustable up to 120 minutes or for continuous operation with an acoustic alarm to show the cycle has finished. At the end of the set cooking time the heat and the fan are automatically switched off.
- Maximum temperature of 300°C.
- Perfect evenness: guarantees perfect distribution of heat throughout the oven cavity.
- Halogen lighting and "crosswise" pan supports allow clear and unobstructed view of the products being cooked.
- Food temperature probe (available as accessory).
- Drip tray to collect residual cooking juices and fat.
- Drip tray under the door to collect condensed liquid available as accessory.
- Capacity: 6 GN 1/1 trays.



Construction

- Robust structure thanks to stainless steel construction.
- Cooking chamber in 430 AISI stainless steel.
- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Ergonomic door handle.
- Integrated drain outlet.
- 1 pair of 60 mm pitch runners is supplied as standard.
- IPx4 water protection.


APPROVAL: _____

Optional Accessories

- | | | |
|---|------------|--------------------------|
| • Pair of AISI 304 stainless steel grids, GN 1/1 | PNC 921101 | ☐ |
| • Pair of 1/2 GN pan support shelves | PNC 921106 | ☐ |
| • Water softener with salt for ovens with automatic regeneration of resin | PNC 921305 | ☐ |
| • Flue condenser for 10 1/1 and 2/1 GN gas ovens | PNC 921701 | ☐ |
| • Probe for 6-10 1/1 GN ovens | PNC 921702 | ☐ |
| • 1/1 GN drain pan guide kit | PNC 921713 | ☐ |
| • Pair of AISI 304 stainless steel grids, GN 1/1 | PNC 922017 | ☐ |
| • Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 | PNC 922036 | ☐ |
| • AISI 304 stainless steel grid, GN 1/1 | PNC 922062 | ☐ |
| • Open base for 6 GN 1/1 convection oven | PNC 922101 | ☐ |
| • Shelf guides for 6 1/1 GN oven base | PNC 922105 | ☐ |
| • Retractable hose reel water spray unit | PNC 922170 | ☐ |
| • External side spray unit (needs to be mounted outside and includes support to be mounted on the oven) | PNC 922171 | ☐ |
| • Fat filter for 6 GN ovens | PNC 922177 | ☐ |
| • Pair of frying baskets | PNC 922239 | ☐ |
| • Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 | PNC 922266 | ☐ |
| • Kit universal skewer rack and 6 short skewers for Lengthwise GN 2/1 and Crosswise ovens | PNC 922325 | ☐ |
| • Universal skewer rack | PNC 922326 | ☐ |
| • 6 short skewers | PNC 922328 | ☐ |
| • Smoker for lengthwise and crosswise oven | PNC 922338 | ☐ |
| • Drip tray for convection oven 6 GN | PNC 922430 | ☐ |
| • Mesh grilling grid, GN 1/1 | PNC 922713 | ☐ |
| • Non-stick universal pan, GN 1/1, H=20mm | PNC 925000 | ☐ |
| • Non-stick universal pan, GN 1/1, H=40mm | PNC 925001 | ☐ |
| • Non-stick universal pan, GN 1/1, H=60mm | PNC 925002 | ☐ |
| • Double-face griddle, one side ribbed and one side smooth, GN 1/1 | PNC 925003 | ☐ |
| • Aluminum grill, GN 1/1 | PNC 925004 | ☐ |
| • Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1 | PNC 925005 | ☐ |

Front

Side


CW11 = Cold Water inlet 1 (cleaning) **G** = Gas connection
CW12 = Cold Water Inlet 2 (steam generator)
D = Drain
EI = Electrical inlet (power)

Top


Electric

Supply voltage:

240470 (ZFCG61CSAS)

220-230 V/1 ph/50 Hz

Electrical power max.:

0.35 kW

Gas

Gas Power:

8.5 kW

Capacity:

Trays type:

6 - 1/1 Gastronorm

Shelf capacity:

6

Key Information:

External dimensions, Width:

860 mm

External dimensions, Depth:

746 mm

External dimensions, Height:

701 mm

Net weight:

92.1 kg

Functional level:

Basic

Runners pitch:

60 mm

Cooking cycles - air-convection:

300 °C

Heating-up time (hot air cycle):

215°C / 350s.